




TYPICAL APPLICATION:
SECURING UPHOLSTERY-COVERED
PANELS



©2002 DUPREE, INC.

PART NO. EXAMPLE: **OHCW 4SM 10 D S01YE** =

82° OVAL HEAD SCREW w/CAPTIVE NYLON WASHER,
SHEET METAL, 4-24 X 5/8 LONG, STEEL, PHILLIPS DRIVE,
SEMI-GLOSS YELLOW PER FED. STD. 595 NO. 26555

HEAD TYPE	THREAD			L LENGTH TOL.±.03						MATERIAL	COLOR CODE	DIM DATA ±.020			
	CODE	NOMINAL DIAMETER	PITCH	1/4	3/8	1/2	5/8	3/4	1			A	B	C	D
OHCW	4SM	4	24	4	6	8	10	12	16	D STEEL PHILLIPS DRIVE	SEE FORWARD SECTION FOR STOCK COLOR & CODE	.300	.025	.272	.089

FEATURES:

1. The one piece screw and captive washer simplifies handling, installation and removal of attachment hardware.
2. Attachment hardware, color matched with the mounting surface eliminates distraction from the information display by blending with the background.
3. Screw heads are formed by cold forging, followed by a case hardening and heat treating process which increases the basic tensile strength of the material. The resultant high tensile strength thus eliminates burring and yield of the substrate under the coating material.
4. The thermosetting coating material used in combination with the relatively hard screw heads is resistant to abrasion and screw driver damage. This feature virtually eliminates the need for touch up painting after assembly.
5. The nylon washer provides a resilient cushion to protect the finished surface of panels and equipment.
6. A self-locking feature to prevent vibration from loosening the screw is achieved by the compression effect of the nylon washer between the screw head and the mounting surface.
7. A seal for moisture, low pressure gases and vapors can be affected between the screw head and the mounting surface by the compression of the nylon washer.
8. Type 'AB' thread style offers a fine pitch thread with a sharp gimlet point which aids entry of the screw where hole misalignment could cause problems.

NOTES:

1. The screws listed in this series reflect high quality with emphasis on the forming of the Phillips recess to meet design specification.

2. Care should be exercised to assure that the screw driver tools meet the same quality and design specification in order to eliminate mismatching and subsequent damage to the drive recess and coating material.
3. These screw assemblies are capable of forming mating threads in steel plate with a maximum Rockwell hardness of B70-85 without thread shearing or breakage.
4. These screw assemblies are primarily intended for application in light sheet metal, plywood, certain plastics or material similar in composition where frequent removal is not necessary. They are not recommended for installation into brittle materials.
5. The thread diameters and lengths listed in the table are industry standard sizes. Inventory levels of these sizes may vary at any one time due to customer demands and lead time necessary for production. Lengths not listed are also available on order.

SPECIFICATIONS:

1. Screws are in accordance with ANSI/ASME Standard No. B18.6.4, Recessed Head Tapping Screws, Type AB.
2. Screws are stocked zinc plated per ASTM B633-85, Class SC1, Type II.
3. Washer color is achieved by molding with pigmented nylon per ASTM D 4066-90.
4. Screw head coating and washer colors are matched to customer requirements. We recommend selection from Fed. Std. 595 whenever possible but we are also prepared to match customer furnished color chips or samples.

STAKE FASTENER CO.

14395 RAMONA AVENUE
CHINO, CALIFORNIA 91710

(909) 597-4889
CAGE 12324

FAX (909) 597-3043
sales@stakefastener.com



UPHOLSTERY SCREW

COLORED 82° OVAL HEAD
w/CAPTIVE NYLON WASHER,
SHEET METAL THREAD, ALLOY STEEL